

ODP 333 - Technical features

<u>Print method</u>	<u>direct, thermal</u>
<u>Print speed</u>	<u>160mm/sec</u>
<u>Effective Print Width</u>	<u>72mm / 512 dots/line</u>
<u>Characters per line</u>	<u>Font A: 42 columns, 180dpi</u> <u>Font B : 56 columns, 180dpi / 64 columns, 203dpi</u>
<u>Internal memory</u>	<u>64MB</u>
<u>Motherboard</u>	<u>low power consumption – automatic standby mode</u> <u>enables 30% less power use on average</u>
<u>Paper loading</u>	<u>automatic</u>

Thermal paper

<u>Width</u>	<u>79.5mm +/- 0.5mm</u>
<u>Thickness</u>	<u>0.065 – 0.1mm</u>
<u>Max. roll diameter</u>	<u>83mm</u>

Characters

<u>Alphanumeric</u>	<u>95</u>
<u>Extended graphic</u>	<u>128 x 18 pages</u>
<u>International characters</u>	<u>14</u>
<u>Barcode</u>	<u>UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF,</u> <u>Codabar, 2D PDF417, QR Code</u>
<u>Emulation</u>	<u>ESC/POS compatible</u>
<u>Drivers</u>	<u>Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS</u>
<u>Sensor</u>	<u>end-of-roll, near end-of-roll, cover open</u>
<u>Till output port(s)</u>	<u>1 dual port (for 2 drawers) - RJ11 6-pin connector</u>
<u>Interfaces</u>	<u>Triple interface</u> <u>RS232 Serial - USB & Ethernet dual (non-modifiable)</u>
<u>Power supply</u>	<u>External 24V - 2.5A</u>

Paper cutter

<u>Auto cutter</u>	<u>guillotine type</u> <u>Max. 30 cuts/minute</u>
<u>Cut type</u>	<u>total or partial</u>

Other features

<u>MCBF</u>	<u>35-50 million lines depending on type of use and paper thickness</u> <u>Printer head lifespan: 160km</u> <u>Paper cutter lifespan: Approx. 1.5 million cuts</u>
<u>Operating temperature</u>	<u>-20 to +60°C</u>
<u>Operating humidity</u>	<u>10% to 90% (without condensation)</u>
<u>Dimensions (depth x width x height)</u>	<u>165 x 135 x 105.02mm</u>
<u>Weight</u>	<u>1kg approximately</u>