

IP66 RATED FULLY ILLUMINATED ROCKER SWITCH

INTRODUCING THE NEW RBW2 FULLY ILLUMINATED SEALED ROCKER SWITCH

Finally a fully illuminated power-rated rocker switch that is sealed to IP66 ratings WITHOUT THE BOOT! No rubber boot / PVC cap is needed for our brand new RBW2 series rocker switch. It uses a patented sealing technology (Patent No. US 7,872,205 B2) to provide protection from dust and moisture all while offering full illumination!

Approved under new UL 61058-1 rating.
UL approved up to 1/3 HP

The markets for the new fully illuminated RBW2 series sealed rocker switch include commercial appliances, electrical housewares, floor care appliances, industrial controls, medical equipment and white goods.

The German distributor for the E-Switch RBW2 fully illuminated rocker switch and other components is the Engelking Elektronik GmbH

To find out more about this new product, please contact us today.



Specification

Electrical ratings	16A 125VAC 5E4 T85 [cURus]
	1/3HP 125VAC IP66 [cURus]
	10A 250VAC 5E4 T85 [VDE]
Electrical life	50,000 Cycles
Mechanical life	50,000 Cycles
Contact resistance	< 30mOhm max.
Insulation resistance	500MOhm min. at 500VDC
Dielectric strength	1000VAC for 1 Minute
Operating temperature	-20°C to +85°C min
Ingress protection	IP66
Panel cutout	22mm x 30mm
Functions	DPST, Off-On; DPDT On-On