

## BOXi MP-350 MOBILE PROJECTOR

Radiation Performance	
<b>Brightness</b>	300 ANSI lm
<b>Resolutions</b>	WXGA 1,280×800
<b>Aspect Ratio</b>	16:10
<b>Uniformity</b>	80% (JBMIA)

<b>Lens</b>	F=2.04 f=9.05
<b>Focus</b>	Manual

I/O	
<b>WiFi</b>	IEEE802.11b/g/n

### Input Signal System

<b>RGB Signal Input</b>	640x350 -WSXGA + (1680 X 1050)
-------------------------	--------------------------------

<b>HDMI Input</b>	480i/p, 576i/p, 720p, 1080i/p Supported HDCP
-------------------	--

### Power

<b>AC Adapter</b>	100-240V, 50-60Hz
-------------------	-------------------

<b>Consumed Power</b>	65.4W (ECO mode off) 35W (ECO mode on)
-----------------------	---

### Noise Level

<b>Noise (FAN)</b>	47dB (ECO mode off: Presentation mode) 40dB (ECO mode on)
--------------------	--

### OTHERS

<b>Operation Temperature</b>	5-35 °C
------------------------------	---------

<b>Operation Humidity</b>	85% (Maximum)
---------------------------	---------------

<b>Storage Temperature</b>	-20°C - +60 °C
----------------------------	----------------

<b>Storage Humidity</b>	90% (Maximum)
<b>Demension/ Weight</b>	WDH: 132mmx143mmx43mm / 500g