

PRESS RELEASE

January 2010

New ODP 1000 POS printer from POSLIGNE®: a subtle blend of contemporary minimalist design and black satin lacquer finish

Runcorn & Lisses – January 3rd 2010: The **AURES** Group, which manufactures **POSLIGNE®** point of sale terminals and systems, has unveiled its new thermal receipt printer specially designed for points of sale and service - the **ODP 1000**.

This stylish printer is both elegant and discreet. Its minimalist lines are done out in a deep, intense black, bringing to mind delicate satin and the mirror effect of refined Chinese lacquer.

This receipt printer's highly compact format and small footprint mean that it can find a place at any till point; in addition, its design benefits from a *front-mounted printout*, ensuring it's splash-proof and well-sealed all round – a very worthwhile quality in certain adverse environments where splashes, dust and crumbs are common – *such as kitchens, restaurants and bars in the hotel and catering industry, hospitality sector or bakery outlets*.

POSLIGNE®'s **ODP 1000** boasts a print speed of 160mm/second, automatic paper loading and cutting, and an integrated dual interface (serial and USB ports). It's ready for use out of the box, with all the required cables supplied.





Key features of the ODP 1000

- contemporary black lacquer finish from POSLIGNE®'s 'Black Piano' collection
- highly ergonomic compact format fits anywhere
- receipt output on the front face (rather than on top of the printer) for enhanced splash-proof design
- integrated dual interface: RS232 C serial and USB ports
- print speed: 160mm/sec
- configuration utilities available
- ready out of the box, with all cables supplied.

Print method	direct, thermal
Print speed	160mm/sec
Effective print width	72mm max. (512 dots/line)
Resolution	180dpi x 180dpi
Internal memory	64MB
Characters per line	Font A: 42 columns
	Font B: 56 columns
Paper loading	automatic
Receipt Printout	front (rather than on top)
<u>Thermal paper</u>	
Width	<u>80mm</u>
Thickness	0.065 – 0.1mm
Max. roll diameter	83mm
<u>Characters</u>	
Alphanumeric characters	<u>95</u>
Extended graphic	128 x 18 pages (1 space / page)
International characters	<u>14</u>
Barcodes:	UPC – A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF 417, QR Code
Emulation	ESC/POS compatible
Sensor	end-of-roll
Cashdrawers output-ports	1 dual port (for 2 drawers)
Interfaces	Integrated dual interface: RS232 C serial and USB ports
Power Supply	External 24V -2,5A
Buzzer	<u>Integrated</u>
Auto cutter	1.5m cuts – max. 30 cuts/minute – total or partial cut
MCBF	35 million lines / Printer head lifespan: 160km / Paper cutter lifespan: approx. 1.5 M cuts
Temperature in use	5 to 40°C
Dimensions (D x W x H)	164.34 x 135.85 x 110.03mm
Weight	1.4kg
Drivers	Windows Driver (7, XP, 2000, 2003, Vista, XP, XP Embedded)

Linux, OPOS, WEPOS, Java POS



About the AURES Group

Founded in 1989 and listed on Euronext Paris since 1999, the AURES Group manufactures point-of-sale EPoS terminals and systems as well as related peripherals, which it markets under the POSLIGNE® brand.

Acclaimed for its reliability and performance, this PC-based, open-system hardware is designed to provide management and till functions in specialist food and non-food stores, mass retail outlets, and the hotel and catering industry, as well as all other points of sale and service.

With EPoS featuring innovative designs and a wide range of fully interchangeable colours, the AURES Group is positioned as the most creative leader in its field.

Distribution of POSLIGNE® systems is based out of AURES' headquarters in France, the Group's three subsidiaries in the United Kingdom, Germany and the USA, and a distributor network present in over forty countries.

For further information, please contact **Yannick-Florence WAELLY** +33 (0)1 69 11 16 65 (direct line)

yannick.waelly@aures.com

www.aures.com



POSLIGNE®'s ODP 1000:

Minimalist Lacquered Design & Style: just like a really smart
Sushi Bento Box!

(photos: AURES Technologies)

