

Engelking Elektronik GmbH
Albstrasse 16
D-78609 Tuningen
Germany
Tel: 07464/9865-0
Fax: 07464/9865-71
eMail: info@engelking.de
http://www.engelking.de

NEWS @ ENGELKING

Responsible editor: Samuel Engelking

Release date : immediate

E-SWITCH'S NEW LP2 ILLUMINATED PUSHBUTTON

The new LP2 series illuminated pushbutton switch features multiple LED colors, custom marking options on the caps, and different cap sizes. The LED colors feature red, blue, green, yellow, white and none. You can choose from six different button colors, as well: black, red, white, gray, transparent red, and transparent blue. You can choose your graphic or customize the graphic for the button.



The markets and applications for the LP2 series illuminated pushbutton switch include audio/visual, consumer electronics, telecommunications, medical, testing/instrumentation, computer servers and more.

Specifications:

Operating Life: 300,000 cycles

Contact Rating: 20 VDC @ 1mA; 5VDC @ 5mA Contact Resistance (Initial Max): 200 Ohm max. @ 5VDC, 1mA

Contact Arrangement: SPST, Normally Open

Insulation Resistance: 100 MOhm max. @100VDC

Dielectric Strength (1 min.): 250 VAC

Force: $125 \pm 35 \text{ grams}$ Travel: $1.3 \text{mm} \pm 0.3 \text{mm}$ Operating / Storage Temperature: -20°C to $+70^{\circ}\text{C}$

Engelking Elektronik GmbH

Albstr. 16

D-78609 Tuningen Tel: +49 7464-9865-0 Fax: +49 7464-9865-71

Sales:

Tobias Vosseler Tel: +49 7464-9865-21

www.engelking.de